# This Page Is Inserted by IFW Operations and is not a part of the Official Record

# **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

# IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.

# **Refine Search**

#### Search Results -

Terms	Documents
bridge same receiver same command same bus	32

US Pre-Grant Publication Full-Text Database

US Patents Full-Text Database US OCR Full-Text Database

Database:

EPO Abstracts Database
JPO Abstracts Database
Derwent World Patents Index
IBM Technical Disclosure Bulletins

Search:

L1		Refine Search
	<b>E</b>	

Recall Text Clear

Interrupt

### **Search History**

DATE: Wednesday, June 23, 2004 Printable Copy Create Case

Set Name Query side by side

**Hit Count Set Name** 

result set

DB=USPT, USOC; PLUR=YES; OP=OR

<u>L1</u> bridge same receiver same command same bus

32 <u>L1</u>

END OF SEARCH HISTORY

# **Refine Search**

#### Search Results -

Terms	Documents
L1	0

US Pre-Grant Publication Full-Text Database

US Patents Full-Text Database US OCR Full-Text Database

**Database:** 

**EPO Abstracts Database** 

JPO Abstracts Database Derwent World Patents Index

IBM Technical Disclosure Bulletins

Search:

L2		4
		1

Refine Search





Interrupt

### **Search History**

DATE: Wednesday, June 23, 2004 Printable Copy Create Case

# **Set Name Query**

**Hit Count Set Name** 

side by side

DB=EPAB,JPAB,DWPI,TDBD; PLUR=YES; OP=OR

L2 L1

0 <u>L2</u>

result set

DB=USPT, USOC; PLUR=YES; OP=OR

<u>L1</u> bridge same receiver same command same bus

32 <u>L1</u>

END OF SEARCH HISTORY

32 <u>L1</u>

# **Refine Search**

### Search Results -

	Terms	Docum	ents
	370/402  370/423  370/912  709/230  709/250  709/253  710/52  710/62  10/2  710/33  710/300  710/306  710/313).ccls.		7028
Database:	US Pre-Grant Publication Full-Text Database US Patents Full-Text Database US OCR Full-Text Database EPO Abstracts Database JPO Abstracts Database Derwent World Patents Index IBM Technical Disclosure Bulletins		
Search:	L3 Refine Search	h	
	Recall Text Clear Interrupt		
	Search History		
DATE: Wednesda	y, June 23, 2004 Printable Copy Create Case		
Set Name Query side by side	z nilin veg on on	<u>Hit</u> Count	Set Nam result set
ŕ	C; PLUR=YES; OP=OR 5,307,2,33,300,306,313;709/230,250,253;370/276,401,402,423,912.ccls.	7028	<u>L3</u>
	$,DWPI,TDBD;\ PLUR=YES;\ OP=OR$		
<u>L2</u> L1 <i>DB=USPT,USO</i> (	C; PLUR=YES; OP=OR	0	<u>L2</u>

### END OF SEARCH HISTORY

<u>L1</u> bridge same receiver same command same bus

**Database:** 

L4

# **Refine Search**

#### Search Results -

Terms	Documents	
L1 and L3	1	

US-Pre-Grant-Publication Full-Text-Database
US Patents Full-Text Database
US OCR Full-Text Database
EPO Abstracts Database
JPO Abstracts Database

Derwent World Patents Index
IBM Technical Disclosure Bulletins

Search:

Refine Search

Recall Text 🗢 Clear

Interrupt

## **Search History**

# DATE: Wednesday, June 23, 2004 Printable Copy Create Case

 Set Name Query side by side by side DB=USPT, USOC; PLUR=YES; OP=OR Hit Count result result set
 Set Name Count result set

 DB=USPT, USOC; PLUR=YES; OP=OR 1
 1.4


 1.3
 710/52,62,36,307,2,33,300,306,313;709/230,250,253;370/276,401,402,423,912.ccls.
 7028
 1.3


 DB=EPAB, JPAB, DWPI, TDBD; PLUR=YES; OP=OR 0
 1.2

 DB=USPT, USOC; PLUR=YES; OP=OR 32
 1.1

 L1
 bridge same receiver same command same bus
 32
 1.1

**END OF SEARCH HISTORY** 





IEEE HOME | SEARCH IEEE | SHOP | WEB ACCOUNT | CONTACT IEEE



Publications/Services Standards Conferences Welcome **United States Patent and Trademark Office Quick Links** v » Se. FAQ Terms IEEE Peer Review Welcome to IEEE Xplore® Your search matched 0 of 1046194 documents. O- Home A maximum of 500 results are displayed, 15 to a page, sorted by Relevance O-What Can **Descending** order. I Access? O- Log-out **Refine This Search:** You may refine your search by editing the current search expression or enterior **Tables of Contents** new one in the text box. **Journals** bridge and receiver and command and bus Search & Magazines ☐ Check to search within this result set O- Conference **Proceedings Results Key:** ( )- Standards JNL = Journal or Magazine CNF = Conference STD = Standard Search O- By Author O- Basic Results: Advanced No documents matched your query. Member Services O Join IEEE )- Establish IEEE Web Account

Print Format

 Access the IEEE Member Digital Library

Home | Log-out | Journals | Conference Proceedings | Standards | Search by Author | Basic Search | Advanced Search | Join IEEE | Web Account |
New this week | OPAC Linking Information | Your Feedback | Technical Support | Email Alerting | No Robots Please | Release Notes | IEEE Online
Publications | Help. | FAQ | Terms | Back to Top

Copyright © 2004 IEEE — All rights reserved

IEEE HOME | SEARCH IEEE | SHOP | WEB ACCOUNT | CONTACT IEEE



Membership Publi	cations/Services Standards Conferences Careers/Jobs
	Welcome United States Patent and Trademark Office
Help FAQ Terms I	EEE Peer Review Quick Links Se
Welcome to IEEE Xplore  - Home - What Can - I Access?	Your search matched <b>1</b> of <b>1046194</b> documents.  A maximum of <b>500</b> results are displayed, <b>15</b> to a page, sorted by <b>Relevanc</b> — <b>Descending</b> order.
C- Log-out  Tables of Contents	Refine This Search: You may refine your search by editing the current search expression or enter
O- Journals & Magazines	new one in the text box.  bridge and receiver and command  Search
Conference Proceedings Standards	Check to search within this result set  Results Key:
Search	JNL = Journal or Magazine CNF = Conference STD = Standard
O- By Author O- Basic O- Advanced	1 A method to analyze interference from frequency hopping radios as application to the PROFFAR cosite filter for the Swedish army Carlsson, O.;
Member Services  - Join IEEE - Establish IEEE Web Account	Military Communications Conference, 1989. MILCOM '89. Conference Record. 'Bridging the Gap. Interoperability, Survivability, Security'., 1989 IEEE, 15-1 1989 Pages: 928 - 934 vol.3  [Abstract] [PDF Full-Text (440 KB)] IEEE CNF

Print Format

O- Access the IEEE Member Digital Library

Home | Log-out | Journals | Conference Proceedings | Standards | Search by Author | Basic Search | Advanced Search | Join IEEE | Web Account |
New this week | OPAC Linking Information | Your Feedback | Technical Support | Email Alerting | No Robots Please | Release Notes | IEEE Online
Publications | Help | FAQ| Terms | Back to Top

Copyright © 2004 IEEE - All rights reserved

IEEE HOME | SEARCH IEEE | SHOP | WEB ACCOUNT | CONTACT IEEE

Request Permissions

<u>rightslink()</u>



Membership Publications/Services Standards Conferences

Welcome **United States Patent and Trademark Office** 



FAQ Terms IEEE Peer Review

**Quick Links** 

Search Results [PDF FULL-TEXT 440 KB] DOWNLOAD CITATION

¥

#### Welcome to IEEE Xplore\*

- O- Home
- O-What Can I Access?
- O- Log-out

#### **Tables of Contents**

- Journals & Magazines
- Conference **Proceedings**
- ( )- Standards

#### Search / ...

- ( )- By Author
- O- Basic
- ( )- Advanced

## Member Services

- Join IEEE
- Establish IEEE Web Account
- ( )- Access the **IEEE Member** Digital Library
- Print Format

# A method to analyze interference from frequency he radios and its application to the PROFFAR cosite filt

Carlsson, O.

Telub Teknik AB, Vaxjo, Sweden;

the Swedish army

This paper appears in: Military Communications Conference, 1989. MILC Conference Record. 'Bridging the Gap. Interoperability, Survivability, **1989 IEEE** 

Meeting Date: 10/15/1989 - 10/18/1989

Publication Date: 15-18 Oct. 1989

Location: Boston, MA USA On page(s): 928 - 934 vol.3

Reference Cited: 3

Inspec Accession Number: 3659777

#### Abstract:

A computerized method (called SIGFRID) to simulate the amount of frequency interference in a receiver subjected to a number of interfering transmitters in situation was developed a few years ago. The method handles full scenarios, friendly and hostile distant transmitters, jammers, ambient noise, and propag characteristics. Modeling of important receiver and transmitter properties to analysis of densely colocated radios, as encountered in army vehicles and cor posts, is included. In the present work the author considers the cosite modelii application to the analysis of improvements in cosite performance achieved by PROFFAR cosite filter. It was shown that, using the facilities of SIGFRID, the improvement achieved by using PROFFAR can be readily demonstrated by sul laboratory radio link to the simulated interference

#### **Index Terms:**

frequency agility military computing military systems mobile radio systems radiocon radiofrequency filters radiofrequency interference RFI SIGFRID army vehicles cor posts cosite modeling densely colocated radios frequency hopping radios jamming laboratory radio link receiver interference receiver properties relative range simula interference simulation program transmitter properties

be

#### Documents that cite this document

There are no citing documents available in IEEE Xplore at this time.

Search Results [PDF FULL-TEXT 440 KB] DOWNLOAD CITATION

Home | Log-out | Journals | Conference Proceedings | Standards | Search by Author | Basic Search | Advanced Search | Join IEEE | Web Account | New this week | OPAC Linking Information | Your Feedback | Technical Support | Email Alerting | No Robots Please | Release Notes | IEEE Online | Publications | Help | FAQ| Terms | Back to Top

Copyright © 2004 IEEE — All rights reserved

A 1926

#### First Hit Fwd Refs **End of Result Set**

Generate Collection Print

L1: Entry 1 of 1

File: USPT

Feb 24, 2004

US-PAT-NO: 6697890

DOCUMENT-IDENTIFIER: US 6697890 B1

TITLE: I/O-node-for-a-computer-system-including-an-integrated-I/O-interface

DATE-ISSUED: February 24, 2004

INVENTOR-INFORMATION:

NAME

CITY

STATE

ZIP CODE

COUNTRY

Gulick; Dale E. Hewitt; Larry D.

Austin Austin TX

ASSIGNEE-INFORMATION:

NAME

CITY

STATE ZIP CODE COUNTRY TYPE CODE

Clear

Advanced Micro Devices, Inc.

Sunnyvale CA

02

APPL-NO: 10/ 034878 DATE FILED: December 27, 2001

INT-CL: [07] G06 F 13/12

US-CL-ISSUED: 710/62; 710/33, 710/36, 710/106, 709/201, 709/230 US-CL-CURRENT: 710/62; 709/201, 709/230, 710/106, 710/33, 710/36

Search Selected

FIELD-OF-SEARCH: 710/1, 710/15, 710/17, 710/18, 710/29, 710/31, 710/33, 710/36, 710/38, 710/41, 710/62, 710/64, 710/72, 710/105, 710/106, 712/29, 712/225, 709/201, 709/230

PRIOR-ART-DISCLOSED:

#### U.S. PATENT DOCUMENTS

Search ALL

PAT-NO	ISSUE-DATE	PATENTEE-NAME	US-CL
5432907	July 1995	Picazo, Jr. et al.	395/200
5490168	February 1996	Phillips et al.	375/224
5812930	September 1998	Zavrel	455/5.1
5859848	January 1999	Miura et al.	370/395
6278532	August 2001	Heimendinger et al.	
6282714	August 2001	Ghori et al.	725/81

h e b b g ee e f c h

e ge 

 ☐
 6359907
 March 2002
 Wolters et al.
 370/485

 ☐
 6414525
 July 2002
 Urakawa

 ☐
 6532283
 March 2003
 Ingram
 379/130

#### OTHER PUBLICATIONS

U.S. patent application Ser. No. 09/978,349, filed Oct. 15, 2001. U.S. patent application Ser. No. 10/093,146, filed Mar. 7, 2002.

ART-UNIT: 2182

PRIMARY-EXAMINER: Gaffin; Jeffrey

ASSISTANT-EXAMINER: Mai; Rijue

ATTY-AGENT-FIRM: Meyertons Hood Kivlin Kowert & Goetzel, P.C. Kivlin; B. Noel

#### ABSTRACT:

An I/O node for a computer system including an integrated I/O interface. An input/output node for a computer system that is implemented upon an integrated circuit includes a first transceiver unit, a second transceiver unit, a packet tunnel, a bridge unit and an I/O interface unit. The first transceiver unit may receive and transmit packet transactions on a first link of a packet bus. The second transceiver unit may receive and transmit packet transactions on a second link of the packet bus. The packet tunnel may convey selected packet transactions between the first and second transceiver units. The bridge unit may receive particular packet transactions from the first transceiver may transmit transactions corresponding to the particular packet transactions upon a peripheral bus. The I/O interface unit may receive additional packet transactions from the first transceiver unit and may transmit transactions corresponding to the additional packet transactions upon an I/O link.

20 Claims, 2 Drawing figures

# First Hit Fwd Refs End of Result Set

Generate Collection Print

L4: Entry 1 of 1

File: USPT

Jun 20, 2000

US-PAT-NO: 6078976

DOCUMENT-IDENTIFIER: US 6078976 A

TITLE: Bridge-device-that prevents-decrease in the data transfer efficiency-of

buses

DATE-ISSUED: June 20, 2000

INVENTOR-INFORMATION:

NAME

CITY

STATE

ZIP CODE

COUNTRY

Obayashi; Yoshimasa

Kyoto

JΡ

ASSIGNEE-INFORMATION:

NAME

CITY STATE ZIP CODE COUNTRY TYPE CODE

Matsushita Electric Industrial Co., Ltd.

JP

03

APPL-NO: 09/ 102685 [PALM]
DATE FILED: June 23, 1998

FOREIGN-APPL-PRIORITY-DATA:

COUNTRY

APPL-NO

APPL-DATE

JP

9-167332

June 24, 1997

JΡ

10-074706

March 23, 1998

INT-CL:  $[07] \underline{G06} \underline{F} \underline{13/40}$ 

US-CL-ISSUED: 710/128; 710/52, 710/113

US-CL-CURRENT: 710/315; 710/113, 710/310, 710/52

FIELD-OF-SEARCH: 710/100, 710/101, 710/52, 710/113-130, 710/240-244

PRIOR-ART-DISCLOSED:

#### U.S. PATENT DOCUMENTS

Search Selected Search ALL Clear

PAT-NO	ISSUE-DATE	PATENTEE-NAME	US-CL
4939643	July 1990	Long et al.	
<u>5546546</u>	August 1996	Bell et al.	
5584033	December 1996	Barrett et al.	710/105

5659718	August 1997	Osman et al.	
5768548	June 1998	Young et al.	710/129
5778236	July 1998	Gephardt et al.	710/266
5857082	January 1999	Murdoch et al.	710/128

#### OTHER PUBLICATIONS

"Digital Semiconductor 21152 PCI-toPCI Data Sheet," Digital Equipment Corporation, Maynard, MA, Sep. 1997.

ART-UNIT: 271

PRIMARY-EXAMINER: Thai; Xuan M.

ATTY-AGENT-FIRM: Price, Gess & Ubell

#### **ABSTRACT:**

When the use of a receiver the bus is not be acquired in delayed read or posted write, the length of a burst data transfer is limited by the capacity of the buffer in a bridge device. In order to solve this problem, waits are inserted in data output process via a sender bus in delayed read or posted write according to the condition of the receiver bus. As a result, input rate of data into the buffer in the bridge device is kept constant, and the use of the receiver bus can be acquired in the delayed read or the posted write. Data is simultaneously transferred into and from the buffer in the bridge device, so that the probability of burst data transfer with a long burst data transfer length is increased.

16 Claims, 11 Drawing figures

